



# ***Screwdrivers***

**Call Today to Order • 800-521-8104**



**MP-0909-ST**  
**Adjustable Clutch Screwdriver**

This tool provides full power performance with little maintenance. Ideal for production use where maximum power output is needed. Reversible with pressure actuated trigger. Includes suspension bail hook for use with a tool balancer.

Bit Capacity	Torque Range	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Consumption
1/4" Hex	10-30 in-lbs	1500 rpm	8-1/4"	1.33 lbs	1/4"	3/8"	4 cfm



**MP-800-ST**  
**Adjustable Clutch Screwdriver**

Industrial, rear exhaust screwdriver is equipped with a quick change chuck for greater ease. An adjustable clutch provides a high degree of torque control through internal spring tension. Ideal for most applications. Reversible with pressure actuated trigger. Includes suspension bail hook for use with a tool balancer.

Bit Capacity	Torque Range	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Consumption
1/4" Hex	30-70 in-lbs	1800 rpm	9-1/2"	2.5 lbs	1/4"	3/8"	4 cfm



MP-201AS-ST

**Pistol Automatic Shut-Off Screwdrivers**

These torque control screwdrivers are compact, lightweight, and quiet. The die cast aluminum housing, cushioned ergonomic handle, and balanced design combine to reduce operator fatigue. Features an easy to operate fwd/rev switch, integrated suspension bail attachment, and includes three springs to adjust the torque range to the application.

Model	Bit Capacity	Torque Range	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Consumption
MP-200AS-ST	1/4" Hex	4-45 in-lbs	600 rpm	8-3/4"	1.98 lbs	1/4"	3/8"	4 cfm
MP-201AS-ST	1/4" Hex	3-40 in-lbs	1000 rpm	8-5/16"	1.80 lbs	1/4"	3/8"	4 cfm



### MP-7855-ST

#### Adjustable Clutch Screwdriver

Adjustable, cushion type clutch provides adjustable automatic torque control through internal spring tension on clutch jaws. This general purpose clutch is suitable for most applications.

Bit Capacity	Torque Range	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Consumption
1/4" Hex	30-70 in-lbs	1800 rpm	8-1/8"	2.4 lbs	1/4"	3/8"	4 cfm



### MP-83-7251F

#### Adjustable Clutch Screwdriver

Clutch provides adjustable torque control through internal spring tension on clutch jaws. Cushioned ergonomic handle and easy to operate fwd/rev switch helps reduce operator fatigue. This general purpose clutch is suitable for most applications.

Bit Capacity	Torque Range	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Consumption
1/4" Hex	40-85 in-lbs	800 rpm	8-3/8"	3.1 lbs	1/4"	3/8"	4 cfm



### MP-9905-ST

#### Adjustable Clutch Screwdriver

Lightweight screwdriver perfect for small parts rebuilding, metal and wood component work. Adjustable torque control is easily changed by tightening or loosening the control spring.

Bit Capacity	Torque Range	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Consumption
1/4" Hex	20-60 in-lbs	1800 rpm	7-3/4"	2.3 lbs	1/4"	3/8"	4 cfm



## MP-0955-ST

### Positive Clutch Screwdriver

Positive clutch screwdriver provides manually controlled clutch engagement and release by operator pressure on the tool. Ideal for applications where pull-up conditions require greater running torque than final torque. Great for overcoming difficult screwdriving jobs.

Bit Capacity	Torque Range	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Consumption
1/4" Hex	45-115 in-lbs	1800 rpm	7"	2.3 lbs	1/4"	3/8"	4 cfm



MP-527DD

### Direct Drive Screwdrivers

General purpose screwdrivers featuring durable planetary gearing. Ideal for maintenance and assembly work. Equipped with QC-50 screwdriver attachment.

Model	Bit Capacity	Torque Range	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Consumption
MP-525DD	1/4" Hex	19-55 in-lbs	2000 rpm	6-1/2"	2.25 lbs	1/4"	3/8"	4 cfm
MP-527DD	1/4" Hex	35-75 in-lbs	800 rpm	7-1/2"	3.0 lbs	1/4"	3/8"	4 cfm



## MP-5422

### 1/4" Hex QC Impact Screwdriver

The pistol grip, high-speed, 1/4" hex impact driver is ideal for long run down applications in furniture or products constructed of wood. The RV industry and high-speed assembly lines prefer this tool for quick installation of fasteners. Rubber coated ergonomic handle, well balanced tool comes with left or right side belt clip and left- or right-handed biased fwd/rev mechanism as well as 360° directional exhaust.

Bit Capacity	Bolt (Fastener)	Torque Range	Free Speed Forward	Free Speed Reverse	Head Height	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Consumption
1/4" Hex	3/16"-1/2"	70 ft-lbs	10,000 rpm	7500 rpm	6-1/2"	6-1/4"	2.3 lbs	1/4"	3/8"	7 cfm

### Screwdriver Bit Adapters - Quick Change

Model	Shank Size	Threaded Mount
QC-50	1/4" Hex	3/8"-24
QC-51	7/16" Hex	3/8"-24



QC-50



QC-51