

Concrete Vibrators & Roto Hammer Accessories



NPK®

Nippon Pneumatic **NRV-70**

Concrete Vibrator



Powerful, high-frequency vibrators for compaction of concrete to produce dense concrete. Ideal for pours of low slump concrete in walls, columns and close quarters. Rugged, efficient, and easily maneuvered. **All vibrators are equipped with 8 ft. exhaust hose.**



Roll Throttle

Vibrating Force	658 kg-F	Head Weight	25.3 lbs.
Vibrations Per Minute.....	11500	Air Inlet Thread	3/8"
Head Diameter.....	3"	Air Consumption.....	45 cfm
Head Length	15-3/4"		

Chicago Pneumatic **CP-618**

Concrete Vibrator

Designed for mass concrete containing up to 6" aggregate deposited from 8-yard buckets, in gravity dams, large piers, massive walls, etc.



Vibrations Per Minute.....	7000
Net Weight	65 lbs.
Overall Length	50-1/2"
Vibrator Tube Length.....	21"
Vibrator Tube Diameter	5-3/4"
Avg. Air Consumption	85 cfm

SDS-Plus Bits



Designed for drilling concrete, brick, stone and other masonry materials. All tips are exclusively "HL Grade" (HL20) carbide. Each shaft is shot-peened for torque twist protection and annealed shafts help prevent breakage.

SDS-Plus bits fit all rotary hammers with SDS-Plus and Hilti chucks. The maximum energy per hammer blow is delivered through positive drive slots. Special asymmetrical spiral, undercut double fluting design removes debris more efficiently to reduce heat and extend drill life. Drills 15% faster than the average drill bit.

SDS-Plus Shank

Part No.	Size	Drill Depth	Overall Length
90006	3/16"	4"	6"
90007		6"	8"
90004		8"	10"
90008		10"	12"
90010	1/4"	2"	4"
90013		3"	6"
90014		6"	8"
90016		8"	10"
90028		4"	6"
90029	3/8"	6"	8"
90031		8"	10"
90037		4"	6"
90040	7/16"	4"	6"
90041		8"	10"
90043		10"	12"
		4"	6"

SDS-Plus Shank

Part No.	Size	Drill Depth	Overall Length
90048	9/16"	4"	6"
90052	5/8"	4"	6"
90053		6"	8"
90055		10"	12"
90059	3/4"	6"	8"
90060		8"	10"
90061		10"	12"
90063		16"	18"
90065	5/8"	6"	8"
90067		8"	12"
90069		16"	18"
		6"	8"
90071	1"	8"	10"
90076		16"	18"