

Reversible Screwdrivers



NPK®



Nippon Pneumatic Model ND-6SDY

Screwdriver - Impact Type

Heavy-duty straight impact driver for production fastening applications. Features a built-in power regulator and 1/4" slip chuck bit holder.

Screw Capacity	5/16"	Length	7-11/16"
Free Speed	6000 rpm	Weight	2.6 lbs.
Torque Range	159-442 in.-lbs.	Air Inlet Thread	1/4"
Rec'd Hose Size	1/4"	Avg. Air Consumption	5.3 cfm

NPK®



Nippon Pneumatic Model ND-6HSX

Screwdriver - Impact Type

Heavy-duty, high speed, high torque impact driver features a divertible rear exhaust, straight handle and easy to operate lever throttle. Also features a 1/4" slip chuck bit holder for rapid bit change.

Screw Capacity	5/16"	Length	8-11/16"
Free Speed	10500 rpm	Weight	2.1 lbs.
Torque Range	215-575 in.-lbs.	Air Inlet Thread	1/4"
Rec'd Hose Size	1/4"	Avg. Air Consumption	8.8 cfm

NPK®



Nippon Pneumatic Model ND-5LPX

Screwdriver - Impact Type

High speed impacting type screwdriver for heavy-duty production fastening applications. Lightweight and ergonomically balanced with a divertible exhaust for changing positions rapidly.

Screw Capacity	1/4"	Length	6-13/32"
Free Speed	11000 rpm	Weight	1.4 lbs.
Torque Range	160-200 in.-lbs.	Air Inlet Thread	1/4"
Rec'd Hose Size	1/4"	Avg. Air Consumption	5.3 cfm

NPK®



Nippon Pneumatic Model ND-6HPAX

Screwdriver - Impact Type

High torque impact driver featuring a 1/4" slip chuck bit holder for rapid bit change. Lightweight and easy to operate.

Screw Capacity	5/16"	Length	6-11/16"
Free Speed	8000 rpm	Weight	2.2 lbs.
Torque Range	250-575 in.-lbs.	Air Inlet Thread	1/4"
Rec'd Hose Size	1/4"	Avg. Air Consumption	8.8 cfm

NPK®



Nippon Pneumatic Model ND-6LFAX

Screwdriver - Impact Type

High torque pistol impact driver with a rapid forward and reverse thumb lever offers fast rundown of fasteners. Ideal for large wood screws or self-drilling and tapping screws.

Screw Capacity	1/4"	Length	6"
Free Speed	11000 rpm	Weight	1.8 lbs.
Torque Range	215-395 in.-lbs.	Air Inlet Thread	1/4"
Rec'd Hose Size	1/4"	Avg. Air Consumption	8.8 cfm



Michigan Pneumatic Model MP-800-ST

Screwdriver - Adjustable Clutch

Industrial, rear exhaust screwdriver is equipped with a quick change chuck for greater ease. An adjustable clutch provides a high degree of torque control through internal spring tension. Ideal for most applications.

Screw Capacity	1/4"	Length	10"
Free Speed	1800 rpm	Weight	2.5 lbs.
Torque Range	45-115 in.-lbs.	Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"	Avg. Air Consumption	4 cfm



MP-525DD

**Michigan Pneumatic Model MP-525DD
Model MP-527DD**

Screwdriver - Direct Drive

Reversible 1/4" hex nutrunner is ideal for maintenance and assembly. Equipped with QC-50 screwdriver attachment.

Model	MP-525DD	MP-527DD
Torque Range	19-55 in.-lbs.	35-75 in.-lbs.
Free Speed	2000 rpm	500 rpm
Rec'd Hose Size	1/4"	3/8"
Length	6-1/2"	7-1/2"
Weight	2.25 lbs.	3 lbs.



Michigan Pneumatic Model MP-9905-ST

Screwdriver - Adjustable Clutch

Lightweight screwdriver perfect for small parts rebuilding, metal and wood component work. Adjustable torque control is easily changed by tightening or loosening the control spring.

Screw Capacity	1/4"	Length	7-3/4"
Free Speed	1800 rpm	Weight	2.3 lbs.
Torque Range	20-60 in.-lbs.	Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"	Avg. Air Consumption	4 cfm



Michigan Pneumatic Model MP-0955-ST

Screwdriver - Positive Clutch

Positive clutch screwdriver provides manually controlled clutch engagement and release by operator pressure on the tool. Ideal for applications where pull-up conditions require greater running torque than final torque. Great for overcoming difficult screwdriving jobs.

Screw Capacity	1/4"	Length	7"
Free Speed	1800 rpm	Weight	2.3 lbs.
Torque Range	45-115 in.-lbs.	Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"	Avg. Air Consumption	4 cfm



Michigan Pneumatic Model MP-7855-ST

Screwdriver - Adjustable Clutch

Adjustable or cushion type clutch provides adjustable automatic torque control through internal spring tension on clutch jaws. This general purpose clutch is suitable for most applications.

Screw Capacity	1/4"	Length	7"
Free Speed	1800 rpm	Weight	2.5 lbs.
Torque Range	45-115 in.-lbs.	Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"	Avg. Air Consumption	4 cfm

Reversible & Shut-Off Screwdrivers



Michigan Pneumatic Model MP-0909-ST

Screwdriver - Adjustable Clutch

This tool provides full power performance with little maintenance. Ideal for production use where maximum power output is needed. Reversible with pressure actuated trigger.

Screw Capacity	1/4"	Length	8-1/4"
Free Speed	1500 rpm	Weight	1.3 lbs.
Torque Range	10-30 in.-lbs.	Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"	Avg. Air Consumption	4 cfm



Nippon Pneumatic Model SD-4

Screwdriver - Adjustable Clutch

Industrial screwdriver features a push to start mechanism for greater operator control. Adjustable torque control is easily changed by tightening or loosening control spring. Lightweight for industrial applications.

Screw Capacity	3/16"	Length	8-3/4"
Free Speed	2000 rpm	Weight	1.3 lbs.
Torque Range	9-30 in.-lbs.	Air Inlet Thread	1/8"
Rec'd Hose Size	1/4"	Avg. Air Consumption	3 cfm



Michigan Pneumatic Model MP-76-A

Screwdriver - Positive Clutch

Lightweight screwdriver provides industrial quality at a low price. Excellent balance and a high torque mechanism. Good for small parts rebuilding, wood and metal component work, and auto service work. Reversible with pressure actuated trigger.

Screw Capacity	5/32"	Length	7-9/16"
Free Speed	9000 rpm	Weight	2.2 lbs.
Torque Range	12-20 in.-lbs.	Air Inlet Thread	1/8"
Rec'd Hose Size	1/4"	Avg. Air Consumption	3 cfm



Michigan Pneumatic Model MP-000AR2LC12

Screwdriver - Adjustable Clutch

Adjustable or cushion type clutch provides adjustable automatic torque control through internal spring tension on clutch jaws. This general purpose clutch is suitable for most applications.

Screw Capacity	#12	Length	8-3/4"
Free Speed	1850 rpm	Weight	2.25 lbs.
Torque Range	3-14 in.-lbs.	Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"	Avg. Air Consumption	4 cfm



Michigan Pneumatic Model MP-30P-IR

Screwdriver - Adjustable Clutch

Cushion clutch is adjustable for accurate torque control. Once set, it will not tighten beyond the predetermined torque limit. Reduces work spoilage. **Parts are interchangeable with Ingersoll-Rand Model 00AR-2LCX21 screwdrivers.**

Screw Capacity	1/4"	Length	9-5/8"
Free Speed	1300 rpm	Weight	2.438 lbs.
Torque Range	20-90 in.-lbs.	Air Inlet Thread	1/8"
Rec'd Hose Size	3/8"	Avg. Air Consumption	4 cfm

Reversible Shut-Off Screwdrivers



Michigan Pneumatic

Straight Automatic Shut-Off Screwdrivers



MP-ST-1015



MP-ST-1807

Straight Shut-Off Screwdriver Specifications

Model No.	Free Speed	Torque	Length	Weight	Rec'd Hose Size	Air Inlet Thread	Avg. Air Consumption
MP-ST-1011	1100 rpm	2 - 6 in.-lbs.	8"	0.6 lbs.	1/4"	1/8"	5.2 cfm
MP-ST-1015	1500 rpm	3.5 - 8.7 in.-lbs.	8"	0.6 lbs.	1/4"	1/8"	5.6 cfm
MP-ST-1409	900 rpm	9.6 - 17 in.-lbs.	8-1/2"	1.3 lbs.	1/4"	1/8"	7.0 cfm
MP-ST-1807	700 rpm	13 - 34.5 in.-lbs.	9-3/8"	1.8 lbs.	3/8"	1/4"	10.5 cfm
MP-ST-1817	1700 rpm	8.5 - 26 in.-lbs.	9-3/8"	1.8 lbs.	3/8"	1/4"	10.5 cfm
MP-ST-2208	800 rpm	26 - 52 in.-lbs.	10-1/2"	2.5 lbs.	3/8"	1/4"	17.5 cfm

Michigan Pneumatic

Pistol Automatic Shut-Off Screwdrivers



MP-STP-1807



MP-200AS-ST



MP-STP-1011

The STP series torque control screwdrivers are compact and quiet. Die cast aluminum housing and balanced handle design combine to reduce operator fatigue. The STP Series features integrated trigger operated forward-reverse. **Model MP-200AS-ST and Model MP-201AS-ST include two extra springs for different torque ranges, depending on application.**

Pistol Shut-Off Screwdriver Specifications

Model No.	Free Speed	Torque	Length	Weight	Rec'd Hose Size	Air Inlet Thread	Avg. Air Consumption
MP-STP-1011	1100 rpm	2 - 6 in.-lbs.	7"	1.10 lbs.	1/4"	1/4"	7.0 cfm
MP-STP-1015	1500 rpm	3.5 - 8.7 in.-lbs.	7-1/4"	1.40 lbs.	1/4"		7.0 cfm
MP-STP-1409	900 rpm	9.6 - 17 in.-lbs.	7-1/4"	1.80 lbs.	1/4"		10.5 cfm
MP-STP-1807	700 rpm	13 - 34.5 in.-lbs.	8-1/8"	2.40 lbs.	3/8"		17.5 cfm
MP-STP-1817	1700 rpm	8.5 - 26 in.-lbs.	8-1/8"	2.40 lbs.	3/8"		17.5 cfm
MP-STP-2208	800 rpm	26 - 52 in.-lbs.	8-7/8"	2.80 lbs.	3/8"		17.5 cfm
MP-201AS-ST	1100 rpm	3-40 in.-lbs.	8-5/16"	1.80 lbs.	3/8"	1/4"	4.0 cfm
MP-200AS-ST	550 rpm	2-45 in.-lbs.	8-3/4"	1.85 lbs.			

See pages 24-25 for screwdriver accessories.